



Hull construction	Glass reinforced plastic (fibreglass) with core materials and Diolen reinforcement, landing skids and perimeter aluminium strip.
Fan protection	2"/50mm guard to front of duct.
Dry Weight	Approx.770lbs/350kgs depending on spec.
Payload	In excess of 660lbs/300kgs on water, depending on conditions, more possible on land in a reduced performance capacity.
Sealing	Padded seating in 'T' shape arrangement for three/four persons. Clip-in rear 'bench' seat can be removed to provide deck space.
Steering	Handlebars with lever-style throttle control and twist select throttle for lift engine.
Length	13'8"/4.3m (off cushion)
Width	7'0"/2.10m (off cushion)
Height	5'0"/1.5m (off cushion) 5'10"/1.75m (on cushion)
Thrust Engine	'Hoverised' Vanguard air-cooled, V-Twin High-Torque 37bhp engine. 50bhp 'Rampage' engine available for demanding roles, electric start, Maximum 4000rpm.
Lift Engine	'Hoverised' 13.5bhp air cooled engine, electric start, maximum 3200rpm.
Flotation/Buoyancy	Floats and starts on water, positively buoyant when swamped.
Noise	74dbA (25m) at cruising speed. Maximum 78dbA at full power.
Fuel Capacity	7 Gallons/35 litres in removable tank.
Range	Approx, 100miles/160kms, depending on conditions.
Maximum Speed	Approx. 35mph/56km/h depending on surface/wind/load.
Cruising Speed	Approx, 25mph/40km/h depending on surface/wind/load,
Skirt	Neoprene coated nylon in 68 replaceable segments.
Lift	Approx. 10" (25cms) which gives 8" (20cms) obstacle clearance.
Thrust Fan	Six 6Z Blades, 1100mm duct, 93m/s tip speed.
Lift Fan	7 3Z blades in sound deadened compartment.
Flow straighteners	13 concentric, give extra thrust & fan protection.
Lighting	Yellow beacon as standard, navigation lights, all round white light, optional headlights.
Battery/Electric	Single or twin 12v batteries, marine grade wiring, IP66 Switching.
Standard Fittings	Passenger grab handles, towing eye, mooring cleats.
Instruments	GPS Analogue display Speedo, two tachometers, hour meter.
Water Ingress	Two drain plugs to void interior, high capacity bilge pump.
Certification :	Manufacture statement of compliance with 2014 Hovercraft Code of Practice. CE plate of compliance with 2004/108/EC
Storage	Side pockets, under seat storage and rear seat removable to provide deck area.
Engine/Fan frame/ Exhaust/transmission	Stainless steel.

